

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/009814 A1

(51) International Patent Classification⁷: **B60T 8/00**,
7/12, B60L 15/20

[JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA,
1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(21) International Application Number:
PCT/JP2004/011005

(74) Agent: ITEC INTERNATIONAL PATENT FIRM;
Pola-Nagoya Bldg. 9-26, Sakae 2-chome, Naka-ku,
Nagoya-shi, Aichi, 4600008 (JP).

(22) International Filing Date: 26 July 2004 (26.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-203011 29 July 2003 (29.07.2003) JP

(71) Applicant (for all designated States except US): TOY-
OTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toy-
ota-cho, Toyota-shi, Aichi, 4718571 (JP).


(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(72) Inventor; and
(75) Inventor/Applicant (for US only): HOMMI, Akira

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: VEHICLE AND CONTROL METHOD OF VEHICLE SLIP-DOWN VELOCITY



(57) Abstract: In response to detection of a slip-down of a vehicle under restriction of a motor torque T_m^* , which is required for a drive shaft linked with drive wheels, due to the occurrence of a slip caused by spin of the drive wheels on an ascending slope, the technique of the invention multiplies a torque insufficiency by a ratio (reflection ratio β) specified according to a vehicle speed V in a reverse direction, so as to set a brake torque T_b^* . The torque insufficiency corresponds to a difference between the restricted motor torque T_m^* and a balancing torque T_{grad} corresponding to a road surface gradient set according to the relation between an acceleration of the vehicle and a torque output to the drive shaft. The setting of the brake torque T_b^* makes the velocity of the slip-down of the vehicle approach to a preset vehicle speed. The brake torque T_b^* is applied by hydraulic brakes attached to driven wheels, which are different from the drive wheels. The arrangement of the invention regulates the velocity of the vehicle that slips down the ascending slope by the restriction of the motor torque T_m^* .

WO 2005/009814 A1

BEST AVAILABLE COPY



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.